



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/554,927	10/31/2005	Stefan Arthur Budach	W1.2036 PCT-US	2306
7590 Douglas R Hanscom Jones Tullar & Cooper Eads Station PO Box 2266 Arlington, VA 22202			EXAMINER HINZE, LEO T	
			ART UNIT 2854	PAPER NUMBER
			MAIL DATE 12/28/2007	DELIVERY MODE PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

## Office Action Summary

Application No.

10/554,927

Applicant(s)

BUDACH ET AL.

Examiner

Leo T. Hinze

Art Unit

2854

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 31 October 2005.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 55-103 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 55-103 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 31 October 2005 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
- Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some \* c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. ☒ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- \* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO/SB/08)  
Paper No(s)/Mail Date 20051031.
- 4) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date. \_\_\_\_\_
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: \_\_\_\_\_

## DETAILED ACTION

### *Priority*

1. Receipt is acknowledged of papers submitted under 35 U.S.C. 119(a)-(d), which papers have been placed of record in the file.

### ***Claim Rejections - 35 USC § 102***

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

3. Claims 55-63, 65-67, 71-80, 85-90, 92, 93, and 97-103 are rejected under 35 U.S.C. 102(b) as being anticipated by Sainio et al., US 5,412,577 A (hereafter '577).

- a. Regarding claim 55, '577 teaches a device for regulating at least one register in a printing press comprising: at least one printing group (14-18, Fig. 1); at least one forme cylinder (24, Fig. 1), one transfer cylinder (22, Fig. 1) and one counter-pressure cylinder (26, Fig. 1; each forme cylinder acts as a counter-pressure cylinder to another forme cylinder) in said at least one printing group and adapted to print a color image on an imprinting substrate being printed in color in said printing group ("each print one color of the image upon web 12," col. 4, ll. 60-61); an image sensor adapted to record an image of said imprinting substrate (34, 36, 37, Fig. 1); an evaluating unit (32, Fig. 1), said evaluating unit being adapted to receive data of said image recorded during a running

Art Unit: 2854

production of said printing press and to compare said data with reference data of a previously recorded image ("compare the data produced from the reference areas of the reprinting plates during printing plate scanning (pre-press image data) and the data produced by scanning the reference areas of the printed image during printing," col. 9, ll. 16-20) said evaluation unit separating said image into color separations ("computer 32 performs color conversion by multiplying a color separation matrix," col. 10, ll. 22-23); a forme cylinder drive mechanism adapted to be controlled separately from said counter-pressure cylinder assigned to said forme cylinder ("precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28 relative to moving web 12," col. 5, ll. 15-17 – the ability to precisely position each cylinder implies an ability to control each separately); an actuator for said drive mechanism (each drive mechanism inherently has an actuator, as there must be some means of actuating each drive mechanism), said evaluation unit being adapted to generate an actuating command to said actuator to regulate a register in response to said data comparison, said evaluating unit performing a relative position determination of a color separation provided by said data comparison ("controller 30 converts the signals from computer 32," col. 5, ll. 10-11); and a pre-printing stage located upstream, in a direction of travel of said substrate, said printing press, said data of said previously recorded image being correlated with an image recorded in said pre-printing stage (plate scanner 38, Fig. 1; col. 6, ll. 22-26).

b. Regarding claim 56, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches means for supplying ink to said at least

Art Unit: 2854

one forme cylinder, said actuator generating said actuating command to an actuating drive mechanism for said means for supplying ink from said data comparison ("each print one color of the image upon web 12," col. 4, ll. 60-61, the ability to print implies an ink supply device, and a drive mechanism to actuate the ink supply device).

c. Regarding claim 57, '577 teaches a device for controlling register and color density in a printing press comprising: at least one printing group (14-18, Fig. 1) having at least one forme cylinder (24, Fig. 1), one transfer cylinder (22, Fig. 1) and one counter-pressure cylinder (26, Fig. 1; each forme cylinder acts as a counter-pressure cylinder to another forme cylinder), said printing group imprinting a substrate in color ("each print one color of the image upon web 12," col. 4, ll. 60-61); an image sensor usable to record an image of said imprinting substrate and to generate data correlated with said image (34, 36, 37, Fig. 1); an evaluating unit usable to receive said image data and data of a previously generated image (32, Fig. 1), said evaluation unit separating said image data and said previous image data into color separations ("computer 32 performs color conversion by multiplying a color separation matrix," col. 10, ll. 22-23), said evaluating unit further performing a relative positional determination of said image data in relation to said previous image data ("compare the data produced from the reference areas of the reprinting plates during printing plate scanning (pre-press image data) and the data produced by scanning the reference areas of the printed image during printing," col. 9, ll. 16-20); an ink supply to said at least one printing group and having an ink supply drive mechanism ("each print one color of the image upon web 12," col. 4, ll. 60-61, the ability to print implies an ink supply device, and a drive

Art Unit: 2854

mechanism to actuate the ink supply device); a register regulatory drive mechanism ("precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28 relative to moving web 12," col. 5, ll. 15-17 – the ability to precisely position each cylinder implies an ability to control each separately); and means in said evaluating unit for correcting differences detected by said relative positional determination in one of a substrate transport direction and a direction transverse to said transport direction into actuating commands for said ink supply drive mechanism and said register regulatory drive mechanism ("precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28 relative to moving web 12," col. 5, ll. 15-17 – the ability to precisely position each cylinder implies an ability to control each separately).

d. Regarding claim 58, '577 teaches the device of claim 57 as discussed in the rejection of claim 57 above. '577 also teaches wherein said image sensor is directed onto said imprinting substrate ("four cameras focused at the same position 50 of printed web 12," col. 5, ll. 32-33).

e. Regarding claim 59, '577 teaches the device of claim 57 as discussed in the rejection of claim 57 above. '577 also teaches wherein said image sensor covers said imprinting substrate transversely to said transport direction (web 12 appears to travel transversely to the camera 32, Fig. 1).

f. Regarding claim 60, '577 teaches the device of claim 57 as discussed in the rejection of claim 57 above. '577 also teaches a forme cylinder drive mechanism adapted to be controlled separately from said counter-pressure cylinder ("precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28 relative

Art Unit: 2854

to moving web 12,” col. 5, ll. 15-17 – the ability to precisely position each cylinder implies an ability to control each separately).

g. Regarding claim 61, ‘577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. ‘577 also teaches wherein said evaluating unit performs said relative position determination by a correlation method (“correlation circuit 118 multiplies the complex conjugate...,” col. 11, ll. 38-41).

h. Regarding claim 62, ‘577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. ‘577 also teaches wherein said evaluating unit performs said relative position determination by a cross-correlation method (“computer 32 is also programmed to operate as a circuit which performs two-dimensional cross correlations,” col. 11, ll. 8-10).

i. Regarding claim 63, ‘577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. ‘577 also teaches wherein said relative position determination is capable of being performed several times (“computer 32 controls the times at which the cameras of assembly 36 scan the printed image... these times are based upon the rotational position of one of the blanket cylinders,” col. 8, ll. 50-55).

j. Regarding claim 65, ‘577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. ‘577 also teaches wherein said register of said forme cylinder is one of a circumferential register, and a lateral register of said forme cylinder with respect to said transfer cylinder associated with said forme cylinder (“precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28 relative

Art Unit: 2854

to moving web 12,” col. 5, ll. 15-17 – the ability to precisely position each cylinder implies an ability to control each separately).

k. Regarding claim 66, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches wherein said actuator an angular relation of said forme cylinder (“precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28 relative to moving web 12,” col. 5, ll. 15-17).

l. Regarding claim 67, '577 teaches the device of claim 57 as discussed in the rejection of claim 57 above. '577 also teaches a data network (86, Fig. 1) connected to said evaluating unit, said drive mechanisms being correlated to said data network.

m. Regarding claim 71, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches a memory device in said evaluating unit and adapted to store sequences of said recorded image (33, Fig. 1).

n. Regarding claim 72, '577 teaches the device of claim 57 as discussed in the rejection of claim 57 above. '577 also teaches wherein said printing press applies at least one printed image to said imprinting substrate (“each print one color of the image upon web 12,” col. 4, ll. 60-61).

o. Regarding claim 73, '577 teaches the device of claim 57 as discussed in the rejection of claim 57 above. '577 also teaches wherein said regulation is capable of taking place simultaneously with an inspection of said printed image (“system detects print color misregistration based upon the signals produced by the imaging device as a result of scanning the printed image,” abstract; “control a print controller which controls the print units such that the colors of the printed image are placed into registration,”

Art Unit: 2854

abstract; '577 is silent as to the exact correlation between regulation and inspection; but as the machine prints a web, it is implied that scanning and register correction are taking place simultaneously).

p. Regarding claim 74, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches several of said printing groups (14-18, Fig. 1) arranged in said printing press in said direction of transport of said imprinting substrate (12, Fig. 1) and wherein said image sensor is located in an outlet of a last one of said printing groups (see location of camera 36 at outlet of printing group 20, Fig. 1).

q. Regarding claim 75, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches a delivery device for said printing press and wherein said image sensor is located at said delivery device (camera 36 is located at part of press which "delivers" web 12 from printing unit 20, Fig. 1).

r. Regarding claim 76, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches wherein said evaluating unit checks a registration maintenance during said running production of said printing press ("when the printed colors are not in substantial registration .... system 10 is configured to perform a primary registration process," col. 13, ll. 58-67).

s. Regarding claim 77, '577 teaches the device of claim 76 as discussed in the rejection of claim 76 above. '577 also teaches wherein said evaluating unit is capable of checking at least one of a shading change and a registration maintenance during said running production of said printing press ("computer 32 controls the times at which the

cameras of assembly 36 scan the printed image... these times are based upon the rotational position of one of the blanket cylinders," col. 8, ll. 50-55).

t. Regarding claim 78, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches wherein said evaluating unit classifies checked printed copies into groups of different quality (computer 32 causes a registration adjustment when printed copies are found to be classified in the "unacceptable" group, Abstract).

u. Regarding claim 79, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches wherein said evaluating unit is adapted to store data for use in determining quality of printed products (data stored in memory 32, Fig. 1).

v. Regarding claim 80, '577 teaches the device of claim 57 as discussed in the rejection of claim 57 above. '577 also teaches at least one of an imprinting substrate transport device (web 12 is transported through the printing units, Fig. 1) and an imprinting substrate marking device ("each print one color of the image upon web 12," col. 4, ll. 60-61) and means in said evaluating unit for issuing an actuating command to said at least one of said transport device and said marking device when said image data exceeds a permissible tolerance limit ("determine a registration offset between the first and second colors and produces a signal representative of the registration offset," col. 3, ll. 8-10; "precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28 relative to moving web 12," col. 5, ll. 15-17).

Art Unit: 2854

w. Regarding claim 85, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches wherein said evaluating unit is adapted to change at least one register in said printing press to obtain registration accuracy ("precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28 relative to moving web 12," col. 5, ll. 15-17).

x. Regarding claim 86, '577 teaches the device of claim 57 as discussed in the rejection of claim 57 above. '577 also teaches wherein said data of said previously generated image is correlated with said image recorded by said image sensor ("compare the data produced from the reference areas of the reprinting plates during printing plate scanning (pre-press image data) and the data produced by scanning the reference areas of the printed image during printing," col. 9, ll. 16-20).

y. Regarding claim 87, '577 teaches the device of claim 57 as discussed in the rejection of claim 57 above. '577 also teaches a pre-printing device located upstream, in a direction of travel of said imprinting substrate, said data of a previously generated image being correlated with an image generated in said pre-printing stage (plate scanner 38, Fig. 1, is located at an upstream position in the printing process).

z. Regarding claim 88, '577 teaches the device of claim 87 as discussed in the rejection of claim 87 above. '577 also teaches a data processing device in said pre-printing stage and correlated with said evaluating unit, said data processing device transmitting data of previously generated images to said evaluating device ("scan each plate associated with the printing of a particular printed image and determine the

locations in the image at which the colors of the image are being printed,” col. 6, ll. 22-27).

aa. Regarding claim 89, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches including several of said printing groups (14-18, Fig. 1), each said forme cylinder of each said printing group being controlled independently of said forme cylinder of another of said several printing groups (“precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28 relative to moving web 12,” col. 5, ll. 15-17 – the ability to precisely position each cylinder implies an ability to control each separately).

bb. Regarding claim 90, '577 teaches the device of claim 89 as discussed in the rejection of claim 89 above. '577 also teaches wherein said evaluating unit is adapted to set one of mutual angular relation and phase relation of said forme cylinder involved in printing said color image in said imprinting substrate (“precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28,” col. 5, ll. 15-17).

cc. Regarding claim 92, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches wherein said drive mechanism for said forme cylinder is rigidly connected with a shaft of said forme cylinder (“precisely control longitudinal, lateral, and rotational positioning of cylinders 22, 24, 26, 28,” col. 5, ll. 15-17 – the ability to precisely control the cylinder implies a rigid connection).

dd. Regarding claim 93, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches printing groups in said printing press (14-20, Fig. 1) and wherein said counter-pressure cylinders in said several printing groups

Art Unit: 2854

are mechanically connected (counter-pressure cylinders appear to be mechanically connected, Fig 1).

ee. Regarding claim 97, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches wherein said evaluating unit performs an analysis of portions of said printed image using said data of a previously recorded image ("compare the data produced from the reference areas of the reprinting plates during printing plate scanning (pre-press image data) and the data produced by scanning the reference areas of the printed image during printing," col. 9, ll. 16-20).

ff. Regarding claim 98, '577 teaches the device of claim 97 as discussed in the rejection of claim 97 above. '577 also teaches wherein said portions of said printed images are ones with substantially all color ("determine portions (reference areas) of the printed image produced by the C, M, Y, and K printing plates which include all of the colors being printed," col. 6, ll. 40-44).

gg. Regarding claim 99, '577 teaches the device of claim 97 as discussed in the rejection of claim 97 above. '577 also teaches wherein said evaluating device determines portions of individual color components of said printed image ("computer 32 performs color conversion ... to produce a CMYK vector for each pixel," col. 10, ll 21-25).

hh. Regarding claim 100, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches wherein said evaluating unit converts positional differences detected by said relative position determination between color separation provided from said data into at least one actuating command ("determine a

Art Unit: 2854

registration offset between a first and second colors and produces a signal representative of the registration offset," col. 3, ll. 8-10).

ii. Regarding claim 101, '577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 also teaches wherein said evaluating unit is capable of evaluating suitable portions of a special color image different from standard colors of a colored image (it appears that system 10 can evaluate CMYK images, and any other color images, such as RGB, col. 9, ll. 16-20).

jj. Regarding claim 102, '577 teaches the device of claim 97 as discussed in the rejection of claim 97 above. '577 also teaches wherein said evaluating unit stores said printed images in a memory device (33, Fig. 1).

kk. Regarding claim 103, '577 teaches the device of claim 102 as discussed in the rejection of claim 102 above. '577 also teaches wherein said printed images are stored in said memory device at a desired position (memory inherently stores things in a desired position – storage in an undesired position would be inefficient, as then one would not be able to retrieve the information, due to its presence in an undesired location).

### ***Claim Rejections - 35 USC § 103***

4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Art Unit: 2854

5. Claim 64 is rejected under 35 U.S.C. 103(a) as being unpatentable over '577 in view of Kipphan et al., US 6,050,192 A (hereafter Kipphan).

'577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 is silent as to the details of the inking mechanism and whether a dampening system is required.

'577 does not teach a dampening agent supply and means for regulating said dampening agent supply in response to said data comparison.

Kipphan teaches a process and arrangement for controlling a printing machine, including controlling a dampening solution distribution device.

It would have been obvious to a person having ordinary skill in the art at the time the invention was made to modify '577 to include a dampening distribution device as taught by Kipphan, because one having ordinary skill in the art would recognize that the addition of the well-known dampening device may be necessary for certain types of offset printing.

6. Claims 68-70 and 84 are rejected under 35 U.S.C. 103(a) as being unpatentable over '577 in view of Chretienat et al., US 6,810,813 B2 (hereafter Chretienat).

a. Regarding claim 68:

'577 teaches the device of claim 55 as discussed in the rejection of claim 55 above.

'577 does not teach a company network and a connection between said evaluating unit and said company network.

Art Unit: 2854

Chretienat teaches a device and method for controlling registration in a printing press, including a company network and a connection between said evaluating unit and said company network (col. 4, ll. 42-47).

It would have been obvious to a person having ordinary skill in the art at the time the invention was made to modify '577 to include a company network and a connection between said evaluating unit and said company network as taught by Chretienat, because a person having ordinary skill would be able to combine the prior art elements to create a registration system that is remotely adjustable over the network.

b. Regarding claim 69:

'577 teaches the device of claim 55 as discussed in the rejection of claim 55 above.

'577 does not teach an input and output unit adapted to provide correction options for said actuating command, said evaluating unit being in a bidirectional data exchange with said input and output unit.

Chretienat teaches an input and output unit adapted to provide correction options for said actuating command, said evaluating unit being in a bidirectional data exchange with said input and output unit ("touch screen registration control 96," col. 4, ll. 42-47).

It would have been obvious to a person having ordinary skill in the art at the time the invention was made to modify '577 to include an input and output unit adapted to provide correction options for said actuating command, said evaluating unit being in a bidirectional data exchange with said input and output unit as taught by Chretienat,

Art Unit: 2854

because a person having ordinary skill would be able to combine the prior art elements to create a registration system that is remotely adjustable.

c. Regarding claim 70, the combination of '577 and Chretinat teaches the device of claim 69 as discussed in the rejection of claim 69 above. The combination of '577 and Chretinat also teaches a monitor in said input and output unit and adapted to display said recorded image ("touch screen registration control 96," col. 4, ll. 42-47).

d. Regarding claim 84:

'577 teaches the device of claim 57 as discussed in the rejection of claim 57 above.

'577 does not teach means changing said ink supply using said evaluating unit in response to a shading change exceeding a permissible tolerance limit.

Chretinat teaches means changing said ink supply using said evaluating unit in response to a shading change exceeding a permissible tolerance limit ("a different second operational mode is provided to the operator for altering characteristics of the individual pages of the book, such as ink zone control," abstract).

It would have been obvious to a person having ordinary skill in the art at the time the invention was made to modify '577 to include means changing said ink supply using said evaluating unit in response to a shading change exceeding a permissible tolerance limit as taught by Chretinat, because a person having ordinary skill would be able to combine the prior art elements to create a registration system that also adjusts inking parameters.

Art Unit: 2854

7. Claims 81-83 are rejected under 35 U.S.C. 103(a) as being unpatentable over '577 in view of Sainio et al., US 6,796,240 B2 (hereafter '240).

a. Regarding claim 81:

'577 teaches the device of claim 55 as discussed in the rejection of claim 55 above. '577 inherently teaches the computer 32 receiving an angular position signal (the system 10 must know the angular position of the forme cylinder to be able to accurately achieve registration), but is silent as to the device used to provide the signal

'577 does not teach an angle encoder installed on said at least one printing group and adapted to synchronize a frequency of recording of said images with a transport speed of said imprinting substrate.

'240 teaches an angle encoder installed on said at least one printing group and adapted to synchronize a frequency of recording of said images with a transport speed of said imprinting substrate (col. 8, ll. 25-30).

It would have been obvious to a person having ordinary skill in the art at the time the invention was made to modify '577 to include an angle encoder installed on said at least one printing group and adapted to synchronize a frequency of recording of said images with a transport speed of said imprinting substrate as taught by '240, because a person having ordinary skill would be able to combine the prior art and use a well-known encoder to provide angular position signals.

b. Regarding claim 82, the combination of '577 and '240 teaches the device of claim 81, as discussed in the rejection of claim 81 above. The combination of '577 and '240 also teaches wherein said angle encoder is installed in said printing group having said

Art Unit: 2854

image sensor (the encoder would inherently be installed in a printing group to properly provide angular positions of a cylinder in the printing group).

c. Regarding claim 83, the combination of '577 and '240 teaches the device of claim 81, as discussed in the rejection of claim 81 above. The combination of '577 and '240 also teaches wherein said angle encoder transmits an output signal to said evaluating unit ("240: "press encoder signal," col. 8, l. 28).

8. Claims 91 and 94-96 are rejected under 35 U.S.C. 103(a) as being unpatentable over '577.

a. Regarding claim 91:

'577 teaches the device of claim 55 as discussed in the rejection of claim 55 above.

'577 is silent as to the coaxial relationship between said forme cylinder drive mechanism and a shaft of said forme cylinder.

A person having ordinary skill in the art would know that there are only two possible orientations for the shafts of the forme cylinder drive mechanism and a forme cylinder – coaxial or not coaxial.

It would have been obvious to a person having ordinary skill in the art at the time the invention was made to arrange the axes of said forme cylinder drive mechanism and a shaft of said forme cylinder to be coaxial, because a person having ordinary skill in the art would recognize that there are a limited number of variations on the arrangement, and that a coaxial arrangement may provide the most efficient operating parameters.

b. Regarding claim 94:

'577 teaches the device of claim 93 as discussed in the rejection of claim 93 above.

'577 does not teach wherein said counter-pressure cylinder in said several printing groups have a common drive mechanism.

A person having ordinary skill in the art would recognize that the several printing mechanisms could have individual drives or share a common drive, and that each arrangement may have particular advantages or disadvantages.

It would have been obvious to a person having ordinary skill in the art at the time the invention was made to modify '577 to use a common drive mechanism, because a person having ordinary skill in the art would recognize that this may reduce the part count and complexity of the printing machine.

c. Regarding claim 95:

'577 teaches the device of claim 93 as discussed in the rejection of claim 93 above.

'577 does not teach a drive mechanism for said counter-pressure cylinders and being separate from a drive mechanism for said forme cylinders and said transfer cylinders of said several printing groups.

A person having ordinary skill in the art would recognize that the several printing mechanisms could have individual drives or share a common drive, and that each arrangement may have particular advantages or disadvantages.

It would have been obvious to a person having ordinary skill in the art at the time the invention was made to modify '577 to use a drive mechanism for said counter-

Art Unit: 2854

pressure cylinders and being separate from a drive mechanism for said forme cylinders and said transfer cylinders of said several printing groups, because a person having ordinary skill in the art would recognize that this may allow more precise control of each individual form cylinder and transfer cylinder.

d. Regarding claim 96:

'577 teaches the device of claim 55 as discussed in the rejection of claim 55 above.

'577 does not teach wherein said forme cylinder drive mechanism drives said transfer cylinder associated with said forme cylinder.

A person having ordinary skill in the art would recognize that each forme cylinder and transfer cylinder could have individual drives or share a common drive, and that each arrangement may have particular advantages or disadvantages.

It would have been obvious to a person having ordinary skill in the art at the time the invention was made to modify '577 wherein said forme cylinder drive mechanism drives said transfer cylinder associated with said forme cylinder, because a person having ordinary skill in the art would recognize that this may reduce the part count and complexity of the printing machine.


### ***Conclusion***

9. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Leo T. Hinze whose telephone number is 571.272.2864. The examiner can normally be reached on M-F 8-5.

Art Unit: 2854

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Judy Nguyen can be reached on 571.272.2258. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.



Leo T. Hinze  
Patent Examiner  
AU 2854  
17 December 2007



JUDY NGUYEN  
SUPERVISORY PATENT EXAMINER